Material Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name Uses Product Code	 AeroShell Turbine Oil 500 Synthetic lubricating oil for aircraft turbine engines. For further details consult the AeroShell Book on www.shell.com/aviation. 001A0083
Manufacturer/Supplier	: Shell UK Oil Products Limited PO Box 3 Ellesmere Port CH65 4HB United Kingdom
Telephone Fax	: +44-(0) 151-350-4000 : +44-(0) 151-350-4843
Emergency Telephone Number	: +44-(0) 151-350-4595

2. COMPOSITION/INFORMATION ON INGREDIENTS

Preparation description : Blend of synthetic esters and additives.

Hazardous Components

Chemical Name	CAS	EINECS	Symbol(s)	R-phrase(s)	Conc.
Benzenamine, N- phenyl-, reaction products with 2,4,4- Trimethylpentene	68411-46-1	270-128-1	Ν	R51/53	0.10 - 0.90 %
Tricresyl phosphate	1330-78-5	215-548-8	Xn, N	R21/22; R51/53	1.00 - 2.40 %
N-phenyl-1- naphthylamine	90-30-2	201-983-0	Xi, N	R43; R50/53	1.00 - 2.00 %
Additional Inform	nation :	Refer to chap	oter 16 for full	text of EC R-pł	nrases.

3. HAZARDS IDENTIFICATION

EC Classification	: Sensitising. Dangerous for the environment.
Health Hazards	: May cause sensitisation by skin contact. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. May contain mixed isomers of tricresyl phosphate. Tricresyl phosphate may be absorbed either through the skin, by ingestion or by inhalation. These effects are delayed and may be permanent depending upon the degree of exposure.

Effective Date 22.03.2007

according to EC directive 2001/58/EC

Signs and Symptoms Safety Hazards Environmental Hazards	 However, the concentration of these harmful isomers of TCP in this product is so low that neurotoxic effects are not expected. Used oil may contain harmful impurities. Skin sensitisation (allergic skin reaction) signs and symptoms may include itching and/or a rash. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. Not classified as flammable but will burn. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
4. FIRST AID MEASURES	
Inhalation	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
Eye Contact	 Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

Advice to Physician 5. FIRE FIGHTING MEASURES

Ingestion

Material Safety Data Sheet

Clear fire area of all non-emergency personnel.

:

:

Specific Hazards	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Extinguishing Media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable Extinguishing Media	:	Do not use water in a jet.
Protective Equipment for Firefighters	:	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

Treat symptomatically.

In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

Protective measures	:	Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Clean Up Methods	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an

	AeroShell Turbine Oil 500 Version 1.
	Effective Date 22.03.2007
Material Safety Data Sheet	according to EC directive 2001/58/EC
Additional Advice :	absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
7. HANDLING AND STORAGE	
General Precautions :	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Handling :	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Storage :	Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: -50 - 50°C / -58 - 122°F The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance maybe obtained from the local environmental agency office.
Recommended Materials :	For containers or container linings, use mild steel or high
Unsuitable Materials : Additional Information :	density polyethylene. PVC. Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion. Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Exposure Controls	:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
Personal Protective Equipment Respiratory Protection	:	Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker

AeroShell Turbine Oil 500 Version 1. Effective Date 22.03.2007 according to EC directive 2001/58/EC

Material Safety Data Sheet

Hand Protection	 health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN141. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection	 Wear safety glasses or full face shield if splashes are likely to occur. Approved to EU Standard EN166.
Protective Clothing	Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods	 Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Minimise release to the environment. An environmental
Environmental Exposure Controls	assessment must be made to ensure compliance with local environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odour	Yellow to brown. Liquid.Slight hydrocarbon.	
pH	: Not applicable.	
Boiling point	: > 280 °C / 536 °F estimated value(s)	
Pour point	: < -57 °C / -71 °F	
Flash point	: Typical 260 °C / 500 °F (COC)	
Explosion / Flammability	: Typical 1 - 10 %(V)	
limits in air		
Auto-ignition temperature	: > 320 °C / 608 °F	
Vapour pressure	: < 0.5 Pa at 20 °C / 68 °F (estimated value(s))	
Density	: Typical 1,005 kg/m3 at 15 °C / 59 °F	
Water solubility	: Negligible.	
n-octanol/water partition coefficient (log Pow)	: > 6 (based on information on similar products)	
Kinematic viscosity	: Typical 27 mm2/s at 40 °C / 104 °F	
Vapour density (air=1)	: > 1 (estimated value(s))	
Evaporation rate (nBuAc=1)	: Data not available	

Material Safety Data Sheet

10. STABILITY AND REACTIVE	ТҮ
Stability Conditions to Avoid Materials to Avoid Hazardous Decomposition Products	 Stable. Extremes of temperature and direct sunlight. Strong oxidising agents. Hazardous decomposition products are not expected to form during normal storage.
11. TOXICOLOGICAL INFORM	IATION
Basis for Assessment	 Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity	: Expected to be of low toxicity: LD50 >2000 mg/kg , Rat
Acute Dermal Toxicity	: Expected to be of low toxicity: LD50 >2000 mg/kg , Rabbit
Acute Inhalation Toxicity	 This product is not expected to pose an inhalation hazard under conditions of foreseeable use.
Skin Irritation	 Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Irritation	: Expected to be slightly irritating.
Respiratory Irritation	: Inhalation of vapours or mists may cause irritation.
Sensitisation	: Expected to be a skin sensitizer.
Repeated Dose Toxicity	: Not expected to be a hazard.
Mutagenicity	: Not considered a mutagenic hazard.
Carcinogenicity	: Components are not known to be associated with carcinogenic effects.
Reproductive and Developmental Toxicity	: Not expected to be a hazard.
Additional Information	: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity	:	Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Mobility	:	Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Persistence/degradability	:	Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulation	:	Contains components with the potential to bioaccumulate.
Other Adverse Effects	:	Product is a mixture of non-volatile components, which are not

AeroShell Turbine Oil 500 Version 1. Effective Date 22.03.2007 according to EC directive 2001/58/EC

Material Safety Data Sheet

expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal	: Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal	: Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Local Legislation	 Disposal should be in accordance with applicable regional, national, and local laws and regulations. EU Waste Disposal Code (EWC): 13 02 06 synthetic engine, gear and lubricating oils. Classification of waste is always the responsibility of the end user. Hazardous Waste (England and Wales) Regulations 2005.

14. TRANSPORT INFORMATION

ADR

This material is not classified as dangerous under ADR regulations.

RID

This material is not classified as dangerous under RID regulations.

ADNR

This material is not classified as dangerous under ADNR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification		Sensitising. Dangerous for the environment.
EC Symbols	:	Xi Irritant.
EC Risk Phrases	:	R43 May cause sensitisation by skin contact.
		R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
EC Safety Phrases	:	S24 Avoid contact with skin.

AeroShell Turbine Oil 500 Version 1. Effective Date 22.03.2007

according to EC directive 2001/58/EC

Material Safety Data Sheet

EINECS	S37 Wear suitable gloves. S61 Avoid release to the environment. Refer to special instructions/Safety data sheets. All components listed or polymer exempt.
TSCA	: All components listed.
Classification triggering components	Contains N-phenyl-1-naphthylamine.
Other Information	 Environmental Protection Act 1990 (as amended). Health and Safety at Work Act 1974. Consumers Protection Act 1987. Control of Pollution Act 1974. Environmental Act 1995. Factories Act 1961. Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations. Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. Control of Substances Hazardous to Health Regulations 1994 (as amended). Road Traffic (Carriage of Dangerous Substances in Packages) Regulations. Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations. Road Traffic (Carriage of Dangerous Substances in Road Tankers in Tank Containers) Regulations. Road Traffic (Training of Drivers of Vehicles Carrying Dangerous Goods) Regulations. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations. Health and Safety (First Aid) Regulations 1981. Personal Protective Equipment (EC Directive) Regulations 1992. Personal Protective Equipment at Work Regulations 1992.

16. OTHER INFORMATION

R-phrase(s)

R21/22 R43 R50/53 R51/53 R52/53	Harmful in contact with skin and if swallowed. May cause sensitisation by skin contact. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.			
MSDS Version	Number	:	1.	
MSDS Effective	Date	:	22.03.2007	
MSDS Revisior	IS	:	A vertical bar () in the left margin indicates an amendment from the previous version.	
MSDS Regulati	on	:	The content and format of this safety data sheet is in accordance with Commission Directive 2001/58/EC of 27 July 2001, amending for the second time Commission Directive 91/155/EEC.	

AeroShell Turbine Oil 500 Version 1. Effective Date 22.03.2007 according to EC directive 2001/58/EC

Material Safety Data Sheet

Uses and Restrictions	:	This product must be used, handled and applied in accordance with the requirements of the equipment manufacturer's manuals, bulletins and other documentation.
MSDS Distribution	:	The information in this document should be made available to all who may handle the product.
Disclaimer	:	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.