

NEW FTA-250L

Air band Transceiver

Ultra-Compact and Rugged Construction.

Radio Features:

- 5 Watts TX Output Power (Air Band: AM 5W P.E.P., 1.5W carrier)
- Compact Design, Measuring W2.1" x H4.1" x D1.2" (52 x 105 x 30 mm)
- Loud Audio (700 mW)
- 8.33 kHz Narrow Band Compatible
- Noise-Cancelling Function for both Transmit and Receive Audio
- 250 Memory Channels
- Includes High-Capacity Rechargeable Li-ion Battery Pack (7.4 V 1950 mAh)
- External-DC input for Operation and Charging
- AF Pitch Control
- Flip Flop Last Channel Recall
- Dual Watch
- Back-lit Keypad and Display with Dimmer
- PC Programmable (Requires Optional USB Cable: SCU-37)

Supplied Accessories:

Antenna
Belt Clip (SHB-18)
Li-ion Battery Pack (SBR-25LI 7.4V, 1950 mAh)
Charger Cradle (SBH-22)
Cigarette Lighter DC/DC Converter (SDD-12)
Headset Adapter Cable (SCU-15)
Operating Manual
Warranty Card
AC Adapter (SAD-20)

Specifications:

RX Frequency Ranges:	118.000 to 136.975 MHz 161.650 to 163.275 MHz (Weather Channels)*
TX Frequency Ranges:	118.000 to 136.975 MHz
Channel Spacing:	25 kHz/8.33 kHz
TX Emission Type:	AM
RX Emission Type:	AM & FM (FM: for Receiving the Weather Channels)*
RF Power Output:	5.0 W (PEP), 1.5 W (Carrier Power)
Case Size (W x H x D):	52 x 105 x 30 mm w/o Knob & Antenna
Weight:	300 g w/ SBR-25LI, Antenna and Belt Clip
Warranty:	3 Years

* Only available in NOAA weather service areas



FTA-250L