

Revision Date: 16 November 2010 Supercedes: 8 September 2010

Section 1 – Identity of the Substance/Preparation and Company/Undertaking

Product Name: LPS 2 (BULK LIQUID)

Part Numbers: M02005, M02025, M02205

Product Use: A lubricant designed to displace moisture from mechanical and electrical

equipment, provide heavy-duty lubrication and rust prevention.

Supplier: Geocel Limited, Western Wood Way, Langage Science Park, Plympton,

Plymouth, PL7 5BG United Kingdom

TEL: +44 (0)1752 202060

FAX: +44 (0)1752 334384

In Case of Emergency: +001 703-527-3887

Manufacturer: LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)

http://www.lpslabs.com

Section 2 – Hazards Identification

Human and Environmental Hazards This preparation is considered hazardous according to European Union Directives 67/548/EEC and 1999/45/EC.

Harmful: may cause lung damage if swallowed. Inhalation of concentrated petroleum distillate mist or vapours can cause central nervous system (CNS) depression. This product may combust when subjected to high energy ignition sources.

Section 3 – Compositon / Information on Ingredients

INGREDIENT NAME	EC No.	CASRN	Classification	Weight Percent
Distillates (Petroleum), Hydrotreated Light	265-149-8	64742-47-8	[Xn] R65	70 – 80%
Distillates (petroleum), Hydrotreated Heavy Naphthenic	265-155-0	64742-52-5	Note L	20 – 30%

Note L: This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note L in Annex I of 67/548/EEC, and is exempt from a classification of T; R45. (Contains less than 3% DMSO)



Revision Date: 16 November 2010 Supercedes: 8 September 2010

Section 4 - First Aid Measures

Eyes: Liquid contact may cause irritation. Flush eyes with running water for at least 15 minutes, keeping

eyelids open. Get medical attention if irritation persists.

Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do

not use ointments. Seek medical attention if irritation persists.

Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen and get medical attention. If not

breathing, give artificial respiration and get medical attention.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth

to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended.

Seek medical attention immediately.

Section 5 - Fire Fighting Measures

Products of Combustion: Carbon monoxide and carbon dioxide.

General Fire Hazards: High heat will cause product to boil, evolving vapour that could cause explosive rupture of closed containers.

Firefighting media: SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use CO2, water spray, fog or foam. Cool containing vessels with water jet in order

to prevent pressure build-up, autoignition or explosions.

Sensitivity to Impact: None. Sensitivity to Static Discharge: Yes.

Protection Clothing (Fire): Wear protective clothing and equipment suitable for the surrounding fire, including

helmet, face mask, and self-contained breathing apparatus.

Section 6 - Accidental Release Measures

Precautions to protect environment:

Do not allow entry into drains or watercourses. If this occurs inform the local authorities at once.

Spill Cleanup methods:

Eliminate all sources of ignition and ventilate area. Use an absorbent material, eg sand, to mop

up residues. See section 13 'Disposal Considerations'.

Section 7 – Handling and Storage

Usage Precautions:

None.

Storage Precautions:

Keep in original container at ambient temperatures. . Keep container closed.



Revision Date: 16 November 2010 Supercedes: 8 September 2010

Section 8 - Exposure Controls / Personal Protection

Component	EC No.	UK LT EXP (8 hrs.)	UK ST EXP (15 min.)	Other
Distillates (Petroleum), Hydrotreated Light	265-149-8	Not Established	Not Established	100 ppm 525 mg/m3 Supplier Recommendation
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	265-155-0	Not Established	Not Established	5 mg/m³ACGIH-TLV 10 mg/m³ACGIH-STEL (Oil Mist)

Engineering measures

Normal room ventilation is usually adequate. If necessary, use appropriate local exhaust

ventilation to keep exposures below the regulated limits.

Personal protective equipment

Eye protection Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and

emergency shower facilities are recommended.

Hand protection Use protective gloves conforming to appropriate regulations. Please observe the instructions

regarding permeability and breakthrough time that are provided by the supplier of the gloves. Take into consideration the specific local conditions under which the product is used, such as

the danger of cuts, abrasion and the contact time.

Respiratory protection Typical use of this product under normal conditions does not require the use of respiratory

protection. If extended spraying of product will be made under poor ventilation, use appropriate

organic vapour filtering respirators

Hygiene measures Do not soak clothing with this product and continue working without immediately changing

clothes and washing skin. Do not reuse clothing until it has been laundered. An eyewash

fountain should be available in the work area.

Environmental exposure controls

Soak up puddles of product with absorbent material and dispose of according to local

regulations. Ventilate area to reduce worker exposure to vapours and prevent accumulation of

explosive vapour concentrations.



Revision Date: 16 November 2010 Supercedes: 8 September 2010

Section 9 - Physical and Chemical Properties

Appearance: Liquid Colour: Brown

Odour: Petroleum/Cherry Evaporation Rate: < 0.1 (BuAc = 1)

Solubility Description: <3% Flash Point: >79°C(174°F)

Boiling Point: 195°C(383°F) **Flash Point Method:** Tag-Closed Cup

Specific Gravity

Heat of combustion:

(H2O=1):

0.82-0.86 @ 20 °C

Not established

Decomposition Temperature:

Not established

Vapour Density (air = 1): 4.7

Auto ignition temperature:

>228°C(442°F)

Vapour Pressure: <0.01 kPa @ 20°C dispensed liquid

Flammable limits (estimated):

LOWER: 0.6%

Melting Point: Not applicable

Partition Coefficient

UPPER: 7% <1

....**3**

(octanol/water):

Viscosity:

Not established

pH: Not applicable

Odour Threshold:

< 7 cSt @ 25°C

Volatiles: 92-96%

Section 10 - Chemical Stability and Reactivity

Chemical Stability: Product is stable under recommended storage conditions.

Conditions to Avoid: Exposure to direct sunlight for extended periods. Temperatures in excess of 50°C.

Incompatibility: Reactive or incompatible with oxidizing agents.

Hazardous Decomposition: Combustion will generate smoke, possibly thick and choking, resulting in zero

visibility and combustion products include carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will not occur.

Section 11 - Toxicological Information

Acute and Chronic Toxicity

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

B: Component Analysis

Ingredients	EC No.	LC-50	LD-50
Distillates (Petroleum), Hydrotreated Light	265-149-8	>6.8 mg/L *	>5 g/kg *
Distillates (petroleum), Hydrotreated Heavy Naphthenic	265-155-0	Not established	Not established

^{*} Supplier Data

Note L: This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note L in Annex I of 67/548/EEC, and is exempt from a classification of T; R45. (Contains less than 3% DMSO)



Revision Date: 16 November 2010 Supercedes: 8 September 2010

Section 12 - Ecological Information

Mobility: Semi-volatile. Readily absorbed

into soil.

Persistence and degradability:

Only slightly biodegradable.

Bioaccumulative potential:

No bioaccumulation potential

Other adverse effects:

None known.

Component Information

Acute Aquatic Toxicity

Effect on Organisms	Component	EC No.	Test	Species	Results
Acute Toxicity on Fishes	Distillates (Petroleum), Hydro treated Light	265-149-8	96-hr LC50	Oncorhynchus mykiss	3200 ug/L
Acute Toxicity on Daphnia					
Bacterial inhibition	No Data Available				
Growth inhibition of algae					
Bioaccumulation in fish					

For the 265-149-8 component, no toxicity has been observed in water due to extremely low water solubility. However, hydrocarbon and petroleum distillates are potentially toxic to fresh water and saltwater ecosystems. If material is spilled on soil, some potential toxic effects could occur before biodegradation could remove material.

Section 13 - Disposal Considerations

Disposal: Waste must be disposed of in accordance with national and local environmental control regulations.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate.



Revision Date: 16 November 2010 Supercedes: 8 September 2010

Section 14 – Transportation Information

This product is not regulated by any mode of transportation.

Section 15 – Regulatory Information

Warning Symbol(s):

×

Risk Phrases: R-65 Harmful: may cause lung damage if swallowed.

Safety Phrases: S-2 Keep out of the reach of children.

S-23 Do not breathe vapour / spray.

S-24 Avoid contact with skin.

S-62 If swallowed, do not induce vomiting: seek medical advice immediately and

show this container or label.

Precautionary Phrases:

None.

Section 16 - Other Information

User Notes: The purpose of the above information is to describe this product only in terms of Health and

Safety requirements. The information given therefore, should not be construed as guaranteeing specific properties or specification. Customers should satisfy themselves as to the suitability and completeness of this information for their own particular use, bearing in mind any other Health and Safety legislation or regulations. The information and recommendations in this publication are to the best of our knowledge reliable. However, nothing herein is construed as a warranty or representation. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement

arising out of any such use is to be assumed.

Information

ESIS: European Chemical Substances Information

Sources:

HSE EH40 Occupation Exposure Limits.

Suppliers Safety Data Sheets.

Full R-Phrases: R-65 Harmful: may cause lung damage if swallowed.