

MODEL TWIN RB60A 28V

28V STARTING SYSTEM HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



SUPPLIED WITH UNIT
2 x Charger
Output Cable
Parallel Joining Cable
Twin Trolley
2 x Thermal Protection Bag

OPTIONAL EXTRAS	
Various output cable lengths	
Croc Clips	
Various Connectors	
25A, 50A, 75A or 100A 28V DC power supply	

	TWIN RB 60A 28V
Max amps	3000 (Nom. short circut current) 4600 (Max. short circuit current)
Capacity	54 Amp Hrs @ 10 hr rate
Max Voltage	30V DC
Size (cm)	2 X L 45 x W 10 x H 38
Weight kg	63
Operating Temp.	-40°C - +60°C
Case	Stainless steel
Voltage indictication	Digital to IP65
Auxiliary Protection	Circuit breaker 50A
Output Cable	2 metre heavy duty, NATO connector
Charger	2 X 8 A Electronic universal AC input. Charging time less than 2 hours from 50%
Protection	Reverse polarity warning

- · Totally weather protected.
- · Air transportable, 'Non Hazardous'
- · Maintenance free.
- · Tough and compact.
- · No memory effect.
- · Works in any orientation.
- · High charge retention.
- · Long shelf life.
- · Fast recharge.
- · External charger for prolonged unit life.
- · No cycling.
- · Leak proof.
- · Cells replaceable on condition.
- Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Starts Main Battle Tanks.
- · Starts Armoured Fighting Vehicles.
- Lightweight portable start power at remote locations.