According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : AeroShell Compound 07

Product code : 001A0037

Unique Formula Identifier

(UFI)

: 6642-J0UK-000D-2SW9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Glycol for aircraft de-icing., For further details consult the Aer-

stance/Mixture oShell Book on www.shell.com/aviation.

Uses advised against : This product must be used, handled, and applied in accord-

ance with the requirements of the equipment manufacturer's

manuals, bulletins and other documentation.

This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup-

plier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Shell UK Oil Products Limited

Shell Centre London SE1 7NA United Kingdom

Telephone : (+44) 08007318888

Telefax

Contact for Safety Data : If you have any enquiries about the content of this SDS

Sheet please email lubricantSDS@shell.com

1.4 Emergency telephone number

: +44 (0) 20 7934 7778 (This telephone number is available 24

hours per day, 7 days per week)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Acute toxicity, Category 4, Oral H302: Harmful if swallowed.

Specific target organ toxicity - repeated H373: May cause damage to organs through pro-

exposure, Category 2, Kidney longed or repeated exposure if swallowed.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

H226 Flammable liquid and vapour.

HEALTH HAZARDS:

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or

repeated exposure if swallowed.

ENVIRONMENTAL HAZARDS:

Not classified as environmental hazard according to

CLP criteria.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P270 Do not eat, drink or smoke when using this product.

Response:

P301 + P312 IF SWALLOWED: Call a POISON

CENTER/doctor if you feel unwell.

P370 + P378 In case of fire: Use appropriate media to extin-

guish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

Contains ethanediol.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Intentional abuse, misuse or other massive exposure may cause multiple organ damage and or death.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture of ethylene glycol, water and additives.

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Ethanediol	107-21-1	Acute Tox. 4; H302	85 - 95
	203-473-3	STOT RE 2; H373	
	603-027-00-1	(Kidney)	
	01-2119456816-28		
Ethanol	64-17-5	Flam. Liq. 2; H225	1 - 5
	200-578-6	Eye Irrit. 2; H319	
	603-002-00-5		
	01-2119457610-43,	specific concentration	
	UK-01-8186404962-2	limit	
		Eye Irrit. 2	
		50 %	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal

conditions.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : Remove to fresh air. If rapid recovery does not occur,

transport to nearest medical facility for additional treatment.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Kidney toxicity may be recognized by blood in the urine or increased or decreased urine flow. Other signs and symptoms can include nausea, vomiting, abdominal cramps, diarrhoea, lumbar pain shortly after ingestion, and possibly narcosis and death.

Not considered to be an inhalation hazard under normal conditions of use.

Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blisters.

Ingestion may result in nausea, vomiting and/or diarrhoea. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.

May cause significant renal, respiratory, and CNS toxicity.

May cause significant acidosis.

The preferred treatment is immediate transportation to a medical facility and use of appropriate treatment including possible administration of activated charcoal, gastric lavage and or gastric aspiration. If none of the above are immediately available and a delay of more than one hour is anticipated before such medical attention can be obtained, induction of vomiting may be appropriate using IPECAC syrup (Contraindicated if there are any signs of CNS depression). This should be considered on a case by case basis following specialist advice.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Specific other treatments may include ethanol therapy, fomepizole, treatment of acidosis and haemodialysis. Seek specialist

advice without delay.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Will float and can be reignited on surface water. Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke).

Carbon monoxide may be evolved if incomplete combustion

occurs.

Unidentified organic and inorganic compounds.

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Further information : Keep adjacent containers cool by spraying with water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth

or other containment material.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other

suitable material and dispose of properly.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet. Local authorities should be advised if significant spillages cannot be contained.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Advice on safe handling : Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists. Use only in well-ventilated areas.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Product Transfer : Wait 2 minutes after tank filling (for tanks such as those on

road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering,

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023 9.3 29.07.2024 800001000357 Print Date 30.07.2024

splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Hygiene measures : Exposure to this product should be reduced as low as reason-

ably practicable. Reference should be made to the Health and

Safety Executive's publication "COSHH Essentials".

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage stability

Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat.

Use properly labeled and closable containers.

Keep container tightly closed and in a cool, well-ventilated

place.

Store at ambient temperature.

Refer to section 15 for any additional specific legislation cov-

ering the packaging and storage of this product.

The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency

office.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Suitable material: For container linings, use amine-adduct

cured epoxy paint.

Unsuitable material: Aluminium, PVC.

Container Advice : Polyethylene containers should not be exposed to high tem-

peratures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

See additional references that provide safe handling practices: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethanediol	107-21-1	TWA (Vapour)	20 ppm 52 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub-			
		nose for which there	are concerns that dermal abs	
Ethanediol		TWA (particles)	10 mg/m3	GB EH40
	stances are th	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
Ethanediol		STEL (Vapour)	40 ppm 104 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Ethanediol		STEL	40 ppm 104 mg/m3	2000/39/EC
	Further inform skin, Indicativ		possibility of significant uptak	ke through the
Ethanediol		TWA	20 ppm 52 mg/m3	2000/39/EC
	Further inform skin, Indicativ		possibility of significant uptak	ke through the
Ethanediol		TWA (Vapour)	25 ppm	ACGIH
Ethanediol		STEL (Vapour)	50 ppm	ACGIH
Ethanediol		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	GB EH40
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
Ethanol		STEL	1,000 ppm	ACGIH

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Do not ingest. If swallowed, then seek immediate medical assistance

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Date of last issue: 01.06.2023 Version **Revision Date:** SDS Number:

29.07.2024 800001000357 Print Date 30.07.2024 9.3

It is good practice to wear chemical resistant gloves.

Respiratory protection No respiratory protection is ordinarily required under normal

conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appro-

priate combination of mask and filter.

Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

meeting EN14387 and EN143.

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Liquid at room temperature.

Colour colourless

Odour characteristic

Odour Threshold Data not available

Method: Unspecified pour point

Not applicable

Data not available Melting / freezing point

Initial boiling point and boiling : > 100 °Cestimated value(s)

range

Flammability

Flammability (solid, gas) Data not available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / upper flammability limit Typical 15 %(V)

Lower explosion limit / Lower flammability limit : Typical 3 %(V)

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023 9.3 29.07.2024 800001000357 Print Date 30.07.2024

Flash point : 54.4 °C

Method: Unspecified

Auto-ignition temperature : > 200 °C

Decomposition temperature

Decomposition tempera-

ture

Data not available

pH : Typical 6.9

Concentration: 100 %

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 12.8 mm2/s (20 °C)

Method: Unspecified

Solubility(ies)

Water solubility : completely soluble

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

Data not available

Vapour pressure : Data not available (50 °C)

Relative density : 1.096 (15 °C)

Density : 1.096 kg/dm3 (15.5 °C)

Method: Unspecified

Relative vapour density : > 1

Particle characteristics

Particle size : Data not available

9.2 Other information

Explosive properties : Classification Code: Not classified

Oxidizing properties : Data not available

Evaporation rate : Data not available

Conductivity : This material is not expected to be a static accumulator.

Decomposition temperature : Data not available

Molecular weight : Not applicable

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (rat): > 500 - 2,000 mg/kg

Remarks: Harmful if swallowed.

Acute inhalation toxicity : LC 50 (Rat): > 5 mg/l

Exposure time: 4 h Remarks: Low toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Low toxicity

Components:

Ethanediol:

Acute oral toxicity : LD 50 (Rat, male and female): > 2,000 mg/kg

Method: Acceptable non-standard method.

Remarks: Harmful if swallowed.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 100 milliliters (1/2 cup). This material has also been shown to be toxic and potentially

lethal by ingestion to cats and dogs.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 2.5 mg/l

Exposure time: 6 h
Test atmosphere: Aerosol
Method: Literature data

Remarks: LC50 > 1.0 - <= 5.0 mg/l

LC50 greater than near-saturated vapour concentration. Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 (Mouse, male and female): > 2,000 mg/kg

Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

Ethanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5,000 mg/kg

Method: Test(s) equivalent or similar to OECD Test Guideline

401

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline

403

Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria

are not met.

Skin corrosion/irritation

Product:

Remarks : Slightly irritating to skin.

Based on available data, the classification criteria are not met.

Components:

Ethanediol:

Species : Rabbit

Method : Acceptable non-standard method.

Remarks : Slightly irritating to skin.

Insufficient to classify.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Ethanol:

Species : Rabbit

Method : Test(s) equivalent or similar to OECD Test Guideline 404

Remarks : Based on data from similar materials

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks : Slightly irritating to the eye.

Based on available data, the classification criteria are not met.

Components:

Ethanediol:

Species : Rabbit

Method : Acceptable non-standard method. Remarks : Slightly irritating to the eye.

Insufficient to classify.

Ethanol:

Species : Rabbit

Method : Test(s) equivalent or similar to OECD Test Guideline 405

Result : Irritating to eyes.

Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Product:

Remarks : For respiratory and skin sensitisation:

Not a sensitiser.

Based on available data, the classification criteria are not met.

Components:

Ethanediol:

Species : Guinea pig Method : Literature data

Remarks : Based on available data, the classification criteria are not met.

Ethanol:

Species : Mouse

Method : Test(s) equivalent or similar to OECD Test Guideline 406

Remarks : Based on data from similar materials

Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic

Based on available data, the classification criteria are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Components:

Ethanediol:

Genotoxicity in vitro : Method: OECD Test Guideline 471

Remarks: Based on data from similar materials

Method: Acceptable non-standard method. Remarks: Based on data from similar materials

Method: Literature data

Remarks: Based on data from similar materials

Genotoxicity in vivo : Species: Rat

Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Ethanol:

Genotoxicity in vivo : Species: Mouse

Method: OECD Test Guideline 478

Remarks: Based on data from similar materials

Based on available data, the classification criteria are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity

Product:

Remarks : Not a carcinogen.

Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

: This product does not meet the criteria for classification in

categories 1A/1B.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Components:

Ethanediol:

Species : Mouse, male and female

Application Route : Oral

Method : Literature data

Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Ethanol:

Species : Rat, male and female

Application Route : Oral

Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

This product does not meet the criteria for classification in

categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Ethanediol	No carcinogenicity classification.
Ethanol	No carcinogenicity classification.

Material	Other Carcinogenicity Classification
Ethanol	IARC: Group 1: Carcinogenic to humans

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair

fertility.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Components:

Ethanediol:

Effects on fertility : Species: Rat

Sex: male and female Application Route: Oral

Method: Literature data

Remarks: Based on available data, the classification criteria

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: 9.3 29.07.2024

SDS Number: 800001000357

Date of last issue: 01.06.2023

Print Date 30.07.2024

are not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

Ethanol:

Effects on fertility : Species: Mouse

Sex: male and female Application Route: Oral

Method: Equivalent or similar to OECD Test Guideline 416 Remarks: Based on available data, the classification criteria

are not met.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

STOT - single exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

Components:

Ethanediol:

Remarks : Inhalation of vapours or mists may cause irritation to the res-

piratory system.

Based on available data, the classification criteria are not met.

Ingestion may cause drowsiness and dizziness.

Ethanol:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks : Kidney: can cause kidney damage.

Components:

Ethanediol:

Exposure routes : Oral Target Organs : Kidney

Remarks : May cause damage to organs or organ systems through pro-

longed or repeated exposure.

Ethanol:

Remarks : Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Repeated dose toxicity

Components:

Ethanediol:

Species : Rat, male Application Route : Oral

Method : Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs : Kidney

Ethanol:

Species : Rat, male and female
Method : OECD Test Guideline 408

Remarks : No significant adverse effects were reported

Aspiration toxicity

Product:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

Components:

Ethanediol:

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Slightly irritating to respiratory system.

Remarks : Classifications by other authorities under varying regulatory

frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representa-

tive of the product as a whole, rather than for individual com-

ponent(s).

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Components:

Ethanediol:

Remarks : Classifications by other authorities under varying regulatory

frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants : Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

Toxicity to microorganisms

Remarks: Data not available

Components:

Ethanediol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 72,860 mg/l

Exposure time: 96 h

Method: Other guideline method. Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202 Remarks: Practically non toxic:

LC/EC/IC50 > 100 mg/l

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 6,500 -

13,000 mg/l

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Exposure time: 96 h

Method: Other guideline method. Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l

Toxicity to microorganisms : EC20 (Activated sludge, domestic waste): > 1,995 mg/l

Exposure time: 0.5 h

Method: Other guideline method. Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l

Toxicity to fish (Chronic tox-

icity)

NOEC: 15,380 mg/l Exposure time: 7 d

Species: Pimephales promelas (fathead minnow)

Method: Other guideline method. Remarks: NOEC/NOEL > 100 mg/l

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 8,590 mg/l Exposure time: 7 d

Species: Chironomus sp. (midge) Method: Other guideline method. Remarks: NOEC/NOEL > 100 mg/l

Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 14,200 mg/l

Exposure time: 96 h

Method: Test(s) equivalent or similar to OECD Guideline 203 Remarks: Based on available data, the classification criteria are not

met.

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l

Exposure time: 48 h

Method: Test(s) equivalent or similar to OECD Guideline 202 Remarks: Based on available data, the classification criteria are not

met.

Toxicity to algae/aquatic plants : EC50 (Chlorella vulgaris (Fresh water algae)): 675 mg/l

Exposure time: 72 h

Method: Test(s) equivalent or similar to OECD Test Guideline

201

Remarks: Based on available data, the classification criteria are not

met.

Toxicity to microorganisms : Toxic threshold (Pseudomonas putida): 6,500 mg/l

Exposure time: 16 h

Toxicity to fish (Chronic tox-

icity)

NOEC: 245 mg/l

Exposure time: 30 d

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: NOEC/NOEL > 100 mg/l

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 2 mg/l Exposure time: 10 d

Species: Ceriodaphnia dubia (Water flea)

Method: Test(s) equivalent or similar to OECD Guideline 211 Remarks: NOEC/NOEL > 1.0 - <=10 mg/l (based on test data)

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Readily biodegradable.

Components:

Ethanediol:

Biodegradability : Biodegradation: 90 - 100 %

Exposure time: 10 d

Method: OECD Test Guideline 301A Remarks: Readily biodegradable.

Ethanol:

Biodegradability : Biodegradation: 84 %

Exposure time: 20 d

Method: Test(s) equivalent or similar to OECD Guideline 301

В

Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Components:

Ethanediol:

Bioaccumulation : Remarks: Does not have the potential to bioaccumulate significant-

ly.

Ethanol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-

octanol/water

: log Pow: < 1

12.4 Mobility in soil

Product:

Mobility : Remarks: Liquid under most environmental conditions., If

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: 9.3 29.07.2024

SDS Number: 800001000357

Date of last issue: 01.06.2023

Print Date 30.07.2024

product enters soil, it will be highly mobile and may contami-

nate groundwater., Dissolves in water.

Components:

Ethanediol:

Mobility : Remarks: Disperses in water., If product enters soil, one or

more constituents will be highly mobile and may contaminate

groundwater.

Ethanol:

Mobility : Remarks: Dissolves in water., If product enters soil, it will be

highly mobile and may contaminate groundwater.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture does not contain any REACH registered sub-

stances that are assessed to be a PBT or a vPvB..

Components:

Ethanediol:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

Ethanol:

Assessment : The substance does not fulfill all screening criteria for persis-

tence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to

have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: Does not have ozone depletion potential, photochemical ozone crea-

tion potential or global warming potential.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Components:

Ethanediol:

Additional ecological infor-

mation

: Does not have ozone depletion potential.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses.

contamination.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Do not puncture, cut, or weld uncleaned drums.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local legislation

Waste catalogue

EU Waste Disposal Code (EWC):

Waste Code :

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: 9.3 29.07.2024

SDS Number: 800001000357

Date of last issue: 01.06.2023

Print Date 30.07.2024

16 01 14*

Remarks : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Classification of waste is always the responsibility of the end

user.

Hazardous Waste (England and Wales) Regulations 2005.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : 1170 RID : 1170 IMDG : 1170 IATA : 1170

14.2 UN proper shipping name

ADR : ETHANOL SOLUTION
RID : ETHANOL SOLUTION
IMDG : ETHANOL SOLUTION

IATA : ETHANOL SOLUTION

14.3 Transport hazard class(es)

ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

IMDG

Packing group : III Labels : 3

IATA

Packing group : III Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Additional Information: MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: Product is not subject to Authorisa-

tion under REACH.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Volatile organic compounds (VOC) content: 90 %

Other regulations:

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XVII.

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work and its amendments.

Directive 1994/33/EC on the protection of young people at work and its amendments. Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product is subject to the Control of Major Accident Hazards Regulations 2015 (2015 No. 483) based on Seveso III directive (2012/18/EU).

The components of this product are reported in the following inventories:

REACH : All components listed or polymer exempt.

TSCA : All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H302 : Harmful if swallowed.

H319 : Causes serious eye irritation.

H373 : May cause damage to organs through prolonged or repeated

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

exposure.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids

STOT RE : Specific target organ toxicity - repeated exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Other information : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Expert judgement and weight of evi-

dence determination.

Acute Tox. 4 H302 Expert judgement and weight of evi-

dence determination.

STOT RE 2 H373 Expert judgement and weight of evi-

dence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Use in de-icing and anti-icing fluids

- Professional

Uses - Worker

Title : Use in functional fluids

- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Use in de-icing and anti-icing fluids

- Consumer

Uses - Consumer

Title : Use in functional fluids

- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Exposure Scenario - Worker

30000000696	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in de-icing and anti-icing fluids- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC8b, PROC11 Environmental Release Categories: ERC8d
Scope of process	Ice prevention and de-icing of vehicles, aircraft and other equipment by spraying.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Additional Information	No exposure assessment presented for the environment.		
Section 2.1	Control of Worker Exposure		
Product Characteristics			
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP		
Concentration of the Sub-	Covers percentage substance in the product up to 100%.,		
stance in Mixture/Article	Unless stated otherwise.,		
Frequency and Duration of			
	8 hours (unless stated differently).		
Other Operational Condition			
	ard of occupational hygiene is implemented.		
Assumes use at not more that	an 20°C above ambient temperature (unless stated differently).		
Contributing Scenarios	Risk Management Measures		
Bulk open unloading.	Use dedicated equipment. , or: Ensure material transfers are under containment or extract ventilation.		
Filling/ preparation of	Use drum pumps or carefully pour from container.		
equipment from drums or containers.	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.		
General exposures.(closed systems)	No specific measures identified.		
Material transferselevated	Use dedicated equipment.		
temperature	, or:		
	Ensure material transfers are under containment or extract ventilation.		
Spraying/ fogging by ma-	Apply within a vented cab supplied with filtered air under posi-		
chine applicationelevated temperature	tive pressure and with a protection factor of >20.		

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Spraying/ fogging by manual application	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear suitable coveralls to prevent exposure to the skin. Carry out in a vented booth or extracted enclosure. , or: Wear a respirator conforming to EN140 with Type A/P2 filter or better.		
Equipment maintenance	Drain down system prior to equipment opening or maintenance.		
	Wear suitable gloves tested to EN374.		
Storage.	Store substance within a closed system.		
Section 2.2	Control of Environmental Exposure		
No exposure assessment pro	No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

For some of the Contributing Scenarios workplace exposures have been estimated from measured data.

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO
0 4 4 11 141	

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Exposure Scenario - Worker

30000000695	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in functional fluids- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20 Environmental Release Categories: ERC9a, ERC9b
Scope of process	Use as functional fluids e.g. cable oils, transfer oils, coolants, insulators, refrigerants, hydraulic fluids in professional equipment including maintenance and related material transfers.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100%., Unless stated otherwise.,
Frequency and Duration of	Use
	8 hours (unless stated differently).
Other Operational Conditio	
	ard of occupational hygiene is implemented. in 20°C above ambient temperature (unless stated differently).
Contributing Scenarios	Risk Management Measures
Drum/batch transfers	Use drum pumps or carefully pour from container. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Transfer from/pouring from containers	Use drum pumps or carefully pour from container. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Filling/ preparation of equipment from drums or containers.	Use drum pumps or carefully pour from container. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
General exposures.(closed systems)	No specific measures identified.
Remanufacture of reject articles	Drain down system prior to equipment opening or maintenance. Wear suitable gloves tested to EN374.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Equipment maintenance Storage.	Drain down system prior to equipment opening or maintenance. Wear suitable gloves tested to EN374. Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise	
indicated	

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Exposure Scenario - Consumer

30000001096	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use in de-icing and anti-icing fluids - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC4 Environmental Release Categories: ERC8d
Scope of process	De-icing of vehicles and similar equipment by spraying.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Additional Information	No exposure assessment present	ted for the environment.	
Section 2.1	Control of Consumer Exposure	<u> </u>	
Product Characteristics	•		
Physical form of product	Liquid, vapour pressure > 10 Pa a	at STP	
Concentration of the Substance in Mixture/Article	Covers concentration up to (%): 1	Covers concentration up to (%): 100 %	
Amounts Used			
for each use event, covers a	imount up to (g):	5,000	
Frequency and Duration o	f Use	,	
Covers use up to (days/year		365	
Covers exposure up to (hou		4	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES		
Anti-Freeze and de-icing products Washing car window.	Covers concentrations up to 100	%	
	For each use event, covers amou	int up to 33 g	
	covers use up to 365 day/year		
	Covers use up to 1 times/day of		
	Covers exposure up to 4 hours/e		
	covers skin contact area up to (cr		
	Covers use in room size of 58 m		
	Covers use under typical househousehousehousehousehousehousehouse		
	Covers use at ambient temperatu		
Anti-Freeze and de-icing products Pouring into radiator.	Covers concentrations up to 30 %	%	
	For each use event, covers amou	int up to 5,000 g	
	covers use up to 1 day/year	· · · · · ·	
	Covers use up to 1 times/day of	use	
	Covers exposure up to 0.25 hour		
	covers skin contact area up to (cr		
	Covers use in a one car garage (34 m3) under typical ventila-	

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

tion.
Covers use at ambient temperatures.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The Consexpo model has been used to estimate consumer exposures unless otherwise indicated.	

Section 3.2 - Environment

No exposure assessment presented for the environment.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Cootion 4.4 Hoolth	

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Exposure Scenario - Consumer

Exposure occinante occisante		
30000010840		
SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Use in functional fluids - Consumer	
Use Descriptor	Sector of Use: SU21 Product Categories: PC16 Environmental Release Categories: ERC9a, ERC9b	
Scope of process	Use of sealed items containing functional fluids e.g. transfer oils, hydraulic fluids, refrigerants.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 Pa at STP
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Heat transfer fluids	Covers concentrations up to 30 %
	For each use event, covers amount up to 1,000 g
	covers use up to 200 day/year
	Covers use up to 1 times/day of use
_	Covers exposure up to 0.25 hours/event
_	covers skin contact area up to (cm2): 960 cm2
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use at ambient temperatures.

Section 2.2	Control of Environmental Exposure	
No exposure assessment presented for the environment.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The Consexpo model has been used to estimate consumer exposures unless otherwise	
indicated.	

Section 3.2 -Environment		•	•

No exposure assessment presented for the environment.

Section 4.1 - Health

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE	\neg
OLOTION 4	EXPOSURE SCENARIO	

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Compound 07

Version Revision Date: SDS Number: Date of last issue: 01.06.2023

9.3 29.07.2024 800001000357 Print Date 30.07.2024

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 - Environment

No exposure assessment presented for the environment.